# Chemical Safety Data Sheet

#### Section 1 IDENTIFICATION

**GHS Product identifier:** Toluene diisocyanate. **Other means of identification:** /

Recommended use of the chemical and restrictions on use: This product can be used as a raw

material for the manufacture of polyurethane foams, coatings, rubbers and adhesives.

Supplier's details: MIT-IVY INDUSTRY CO.,LTD

Add: 2-1402,OFFICE BUILDING 2, COMMERCIAL INNER STREET AND OFFICE 1, SHIMAO PLAZE YUNLONG DISTRICT XUZHOUJIANGSU, CHINA

Emergency phone number: /

## Section 2 HAZARDS IDENTIFICATION

## Classification of the substance or mixture:

Acute toxicity, inhalation Category 2

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

Sensitisation, respiratory Category 1

Sensitisation, skin Category 1

Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 (Respiratory tract irritation)

Hazardous to the aquatic environment, long-term hazard Category 3

**GHS Label elements, including precautionary statements:** Symbol:



Signal word: Danger

Hazard statement(s): Fatal if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

Precautionary statement(s):

Prevention:

Obtain, read and follow all safety instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection/ hearing protection. [In case of inadequate ventilation] wear respiratory protection.

Response:

IF ON SKIN: Wash with plenty of water. Specific treatment (see safety data sheet). If skin irritation or rash occurs: Get medical help. Take off contaminated clothing. And wash it before

reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. Specific treatment is urgent (see safety data sheet). If experiencing respiratory symptoms: Get emergency medical help immediately. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help. IF exposed or concerned: Get medical help.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations. Other hazards which do not result in classification: /

# Section 3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration%
Tolylene diisocyanate	26471-62-5	100%

# Section 4 FIRST AID MEASURES

# Description of necessary first aid measures

**If inhaled:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician immediately.

**In case of skin contact:** Wash off with soap and plenty of running water. Consult a physician. **In case of eye contact:** Rinse thoroughly with plenty of running water for at least 15 minutes and consult a physician.

If ingestion: Rinse mouth with water. Consult a physician immediately.

Most important symptoms/effects, acute and delayed: /

Indication of immediate medical attention and special treatment needed, if necessary: /

# Section 5 FIREFIGHTING MEASURES

Suitable extinguishing media: Use dry powder or carbon dioxide to extinguish.

**Special hazards arising from the chemical:** This material is combustible. It may burn at high temperature and fire and release toxic fumes.

**Special protective actions for fire-fighters:** Wear self-contained breathing apparatus for firefighting if necessary. Use water spray to cool unopened containers. In case of fire in the surroundings, use appropriate extinguishing media.

## Section 6 ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** It is recommended that emergency personnel wear gas masks and anti-poison suits. Do not touch the spill directly.

Environmental precautions: Isolate contaminated areas and restrict access.

**Methods and materials for containment and cleaning up:** Small amount of leakage: adsorption with sand or other inert materials. Do not allow products to enter restricted areas such as sewers. A large amount of leakage: building a dike or digging a pit to contain. Transfer to a tank truck or special collector with a pump and transport to a waste disposal site for disposal.

#### Section 7 HANDLING AND STORAGE

**Precautions for safe handling:** There should be sufficient local exhaust in workplace. Operators should be trained and strictly follow the operating procedures. Operators are advised to wear gas masks, anti-poison suits and rubber gloves. Operators should load and unload lightly during handling to prevent damage to the package. There should be leakage treatment equipment in workplace. There may be harmful residues in empty containers.

**Conditions for safe storage, including any incompatibilities:** Store in a cool, dry, well-ventilated warehouse. Keep away from fire and heat. Protect from direct sunlight. The package should be sealed and not exposed to moisture. It should be stored separately from oxidants, flammable materials, etc., and should not be mixed. The storage area should be provided with suitable materials to contain spills.

## Section 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:			
Source	Material name	TWA	STEL
China Occupational Exposure			
Limits for Hazardous Agents in	Tolylene-2,4-diisocyanate	0.1 (mg/m <sup>3</sup> )	0.2 (mg/m <sup>3</sup> )
the Workplace			
Appropriate engineering controls: Close strictly and provide sufficient local exhaust.			
Individual protection measures			
Eye/face protection: Wear a gas m	ask.		
Skin protection: Wear an anti-pois	on suit.		
Respiratory protection: Air respirators should be worn during emergency rescue or evacuation.			
Thermal hazards: /			

#### Section 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, colour etc)	Colorless transparent liquid.
Odour	Odor stimulation.
Odour Threshold	0.35~0.92mg/m <sup>3</sup>
рН	/
Melting point/freezing point	19.5~21.5℃.
Initial boiling point and boiling range	247°C.
Flash point	137°C.
Evaporation rate	/
Flammability (solid, gas)	/
Upper/lower flammability or explosive limits Upper explosion limit: 9.5% (V);	
	Lower explosion limit: 0.9% (V).
Vapour pressure	/
Vapour density	/
Relative density	1.21( water=1).
Solubility(ies)	React with water.
Partition coefficient: n-octanol/water	/
Auto-ignition temperature	/
Decomposition temperature	/

¥ 7.	• 4
VISC	ositv
1 190	USILY

1

Section 10 STABILITY AND REACTIVITY

**Reactivity:** /

Chemical stability: This material is stable in normal temperature.

**Possibility of hazardous reactions:** The substance polymerizes with water and many chemicals in a hazardous way. This generates fire or explosion hazard. On combustion, forms toxic gases. This generates toxic hazard.

Conditions to avoid: Spark, static electricity and high temperature.

Incompatible materials: Flammable materials and oxidizers.

Hazardous decomposition products: Oxycarbides and nitrogen oxides.

Section 11 TOXICOLOGICAL INFORMATION

Information on the likely routes of exposure: Inhaled, swallowed, skin, eyes.

Symptoms related to the physical, chemical and toxicological characteristics: /

Acute health effects: Accidental ingestion of the material may be harmful and cause cough, throat irritation and other symptoms. Fatal if inhaled. Oral intake may cause bellyache, nausea, vomit and other symptoms. This material may produce skin and eyes irritation.

**Chronic health effects:** Repeated or prolonged contact with skin may cause dermatitis. Repeated or prolonged contact may cause skin sensitization. Repeated or prolonged inhalation may cause asthma. This substance is possibly carcinogenic to humans.

Numerical measures of toxicity(such as acute toxicity estimates):

LD50(oral, rat): >2000 mg/kg

LD50(dermal, rabbit): >9400 mg/kg

## Section 12 ECOLOGICAL INFORMATION

<b>Toxicity:</b>			
Endpoint Te	est Duration (	(hr) Species	Value
LC50	96	Fish	0.4mg/L
EC50	48	Crustacea	12.5mg/L
EC50	96	Algae or other aquat	ic plants 3-230mg/L
NOEC	504	Crustacea	$\geq 0.5 mg/L$
<b>Persistence and degradability:</b> Low (Half-life = 1 days).			
<b>Bioaccumulative potential:</b> Low (BCF = 5).			
<b>Mobility in soil:</b> Low (KOC = 9114).			
	<b>00</b> / /		

Other adverse effects: /

## Section 13 DISPOSAL CONSIDERATIONS

**Disposal methods:** Dispose this product by safe burial. Damaged containers are prohibited from being reused and should be buried in the prescribed place.

Section 14 TRANSPORT INFORMATION

UN number: 2078.

UN proper shipping name: TOLUENE DIISOCYANATE. Transport hazard class(es) : 6.1. Packing group, if applicable: II. Environmental hazards: No. Special precautions for user: /

# Section 15 REGULATORY INFORMATION

# **Regulations** :

This safety data sheet is in compliance with the following national standards: GB/T 16483-2008, GB13690-2009, GB18218-2018, GB15258-2009, GB6944-2012, GB190-2009, GB191-2009, GB12268-2008, GB/T 15098-2008, GBZ 2.1-2019, GBZ 2.2-2007 as well as the following national regulations: Dangerous Goods Transport Administrative Regulation, Dangerous Chemicals Safety Administrative Regulation.

# Section 16 OTHER INFORMATION

References	UN Recommendations on the Transport of Dangerous Goods Model		
	Regulations		
	UN Globally Harmonized System of Classification and Labelling of		
	Chemicals		
Form Date	18-November-2020		