

# **EASY GO**

# Easy Clean Paint

### **Description**

Water based acrylic emulsion, high stain resistance and washable interior topcoat.

### **Application Areas**

Suitable for all types of interior surfaces of buildings.

#### Feature and Benefits

- High stain resistance against to ketchup, mayonnaise, mustard, lipstick, crayon, marker (water-based), green grass, oil.
- High scrub resistance.
- Gives high breathability property to applied surfaces.
- Ensures perfect integration with the substrate without cracking, blistering and flacking.
- High color retention with deep white color and excellent opacity.
- Human and environment-friendly product with its odorless property.

#### Technical Information

Content	Acrylic emulsion
Color	Most colors
Appearance	Viscous liquid
VOC Properties	< 50 g/L
Gloss	Class G2
Scrub Resistance	Class S1
Particle Size	Class S1 (TS 7847)
Weight Solid	61±2%
Thinning	Water
Consumption	0,160 - 0,180 L/ m <sup>2</sup>
Recommended Coat	2 coats
Application Tools	Brush / Roller
Drying Time	2 hours to touch 8 hours to full cure



# **EASY GO**

## Easy Clean Paint

## Preparation of substrate

The surface should be dry and cleaned out of dirt, grease, old loose or flaking materials. The old paints must be sanded and removed. The surface should be smoothened by **INPAST** Acrylic Interior Paste. Smoothened surface should be left to dry for 24 hours.

### **Applicatior**

Dilute with 10 % water and apply in two coats. After surface preparation, **PRIME C 1/7** Concentrated Primer is diluted with water in the ratio of 1/7 (1 cup primer / 7 cups water) and applied as a single layer, left to dry for 24 hours. **EASY GO** Easy Clean Paint is applied on the surface in two layers with a roller or brush.

### **Packagino**

15 L/2,5 L plastic bucket

#### Shelf Life

24 months in original, unopened package

#### Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

#### Cleanup Information

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

#### Cautions / Limitations

- Do not overcoat with solvent based materials.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +0°C and above +35°C.
- Avoid heavy traffic for 24 hours.
- Allow 4 weeks before washing or cleaning for full cure.



# **EASY GO**

## Easy Clean Paint

### Health and Safety

**Warning!** Cause eye and skin irritation. If eye contact, flush eyes with water for several minutes and remove contacts if present and easy to do. Get immediate medical attention. If skin contact; wash skin with plenty of soap and water. Get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

**Limited Warranty:** This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.